

TTR Standard Wax 31068/31077/31078

TECHNICAL DATA:

Ink Composition:	Wax for Flat-Head Printers
Print Speed:	Up to 300 mm/s
Receiving Label Media:	For Coated and Uncoated Papers, Vellum and Synthetic Material like PE, PP, PVC, PET, etc.
Resistance:	Heat Resistant up to 68°C, Scratch and Smear, Outstanding Print Results at High Speeds and Low Energy Levels
Print:	Ideal for Printing with Printheads up to 300 dpi.
Backcoating:	Silicon-Based
Base-Film:	Thickness: 4,5 µ +/- 1,0 µ
Ink:	Wax; Melting Point: 68°C
Tape:	Thickness: < 7,5 µ +/- 1,0 µ
Storage Recommendations:	12 Month; 5 – 35°C; 20 – 80 % Relative Humidity
Colours:	 black

"The final result of the print quality strongly depends on various factors such as labelstock material, print speed, print density, temperature or humidity. Novexx Solutions strongly recommends to test the print results under real conditions on-site and in advance".

COMPLIANCE DATA:

RoHS	2002/95/EG Restriction of the use of certain Hazardous Substances in electrical and electronic equipment
REACH	1907/2006/EC Registration, Evaluation, Authorisation and Restriction of Chemicals NOVEXX Solutions is Downstream User and under REACH, Article 33 required to inform you when a Substance of Very High Concern (SVHC) is included in one of our Products
Food Contact	The Thermal Transfer Ribbon is compliant to 1935/2004/EC

If you need more information about compliance, please contact our product compliance team:
ec-regulations@novexx.com

Novexx Solutions GmbH
DEUTSCHLAND

Ohmstrasse 3
D-85386 Eching
Tel. +49 (0)8165 925 299
info.deutschland@novexx.com

www.novexx.com

subject to alterations (04/2016)